

**Report 11302
28 October 1998**

**Integrated Advanced Microwave Sounding Unit-A
(AMSU-A)**

Engineering Test Report

METSAT A1 Signal Processor (P/N: 1331670-2, S/N: F03)

**Contract No. NAS 5-32314
CDRL 207**

Submitted to:

**National Aeronautics and Space Administration
Goddard Space Flight Center
Greenbelt, Maryland 20771**

Submitted by:

**Aerojet
1100 West Hollyvale Street
Azusa, California 91702**

TABLE OF CONTENTS

1.0	INTRODUCTION.....	1
2.0	OBJECTIVE	1
3.0	TEST DATA	1
4.0	TEST	1
5.0	TEST ANOMALIES.....	5
6.0	TEST RESULTS.....	6

1.0 Introduction

This report presents a description of the tests performed, and the test data, for the A1 METSAT Signal Processor Assembly PN: 1331679-2, S/N F03. The assembly was tested in accordance with AE-26754, "METSAT Signal Processor Scan Drive Test and Integration Procedure".

The tests were conducted at room temperature in the AMSU-A test area of building 57. The tests fall into six categories: 1) Continuity, 2) Power Distribution, 3) Digital Processor, 4) Analog Processor, 5) Scan Drive, and 6) Supply Current.

2.0 Objective

The objective is to demonstrate functionality of the signal processor prior to instrument integration.

3.0 Test Data

All test data is presented on the enclosed copies of the test data sheets (TDSs) numbered TDS 1 through TDS 10 (Pages A-2 through A-14). Redlines to the data sheets were necessary and were accomplished in accordance with program directive No. 91. Each change was approved by Quality and the test engineer. Changes were made for the following reasons: 1) Test parameter limits were changed due to design changes in the instrument circuitry, 2) Addition of CCA serial number recording locations, and 3) Correction of a typing error. Also included with the test data sheets is the Manufacturing Assembly Instructions list of the CCA card cage slot assignment record listing each CCA part number and serial number.

4.0 TESTS

4.1 Continuity

A complete continuity test of the backplane wiring is performed at the facility where the wirewrapping of the backplane is done. The continuity tests performed here involve 1) the I/O interface card slots, J301 and J326, 2) the Aerojet added Pre-amp/detector signal cable and connector, 3) the Aerojet added Pre-amp/detector power cable and connector, and 4) chassis return connections. The tests are manual resistance measurements tests. Test data is presented on TDS 1.

4.2 Power Distribution

In these tests supply voltages are input to the signal processor from the Test Relay Unit (TRU) as in normal testing. No CCAs are installed in the signal processor for the tests. The test verifies that the four supply voltages are present on the proper pins of all backplane connectors. The test setup block diagram is shown in Figure 1, and test data is presented on TDS 2.




Figure 1. A1 Signal Processor Test Setup

4.3 Digital Processor

Beginning with this test, CCAs are installed into the card cage as required to perform the test, and then remain installed. At the conclusion of all tests, a complete set of CCAs has been installed. The complete test setup block diagram which is required for performing any of the tests is shown in Figure 2.




Figure 2 Scan Drive Test Set-Up

4.3.1 Memory

In this test, the digital test set is used in place of the CPU CCA to read and verify data of the test PROMs on the "GOLD" Memory CCA. Test data is presented on TDS 3.

4.3.2 CPU

The CPU test requires that the CPU Auxiliary test CCA be installed in place of the Memory CCA. In this test, the RAM and various instructions performed by the CPU are tested. In addition, the waveform of the clock signal to the DC-DC converter is measured at the CLOCK jack on the TRU. Test data is presented on TDS 3.

4.3.3 Scan Control Interface

In this test, input and output ports 0 through 3 are tested. In addition, the disable feature of the input ports is checked out. Test data is presented on TDS 3.

4.3.4 Timing and Control

In this test, the proper time intervals of I/H, DUMP, INTCMPL, TSCMPL, STOP, and ANTENNA STROBE are verified. In addition to the above tests, the test set also checks the input ports 16 and 17, output port #13 (4 MSBs), output port 14, input port #15 (DAC BSY signal), and output port #13 (4 LSBs). Test data is presented on TDS 3.

4.3.5 Spacecraft Interface

In this test, the STE is turned on and initialized. The STE is tested with a series of self-tests to verify the readiness of the STE to test flight hardware. After successfully passing the self-tests, the STE is used to simulate the spacecraft command signals and retrieve limited test data for the remaining signal processor tests. STE test data is presented on TDS 4.

4.3.6 Relay Control

This test verifies the operation of the module power command and the survival heater command. The presence of the +10 volt Interface power is verified. The PLO lock alarm signals, Scan 1 and 2 relay drive and position indicators, and PLO relay drive and relay position indicators are also verified. Test data is presented on TDS 4.

4.4 Analog Processor

4.4.1 Independence of Measurements

This test is performed using the Analog CCA Test Fixture, the Integrate and Dump Filter and the Analog Mux and A/D Converter CCAs. The test gives a measurement of the sample-to-sample crosstalk within a channel, which is dependent on the completeness of the dump of the integration capacitor. Test data is presented on TDS 5.

4.4.2 Integrate/dump filter, radiometric data multiplexing, and digitization tests

In this test, a 2 volt dc signal is input to each integrate and dump filter, and the channel output code from the A/D converter is measured. The integrator output waveform is also displayed on an oscilloscope for verification of timing. Test data is presented on TDS 6.

4.4.3 Temperature monitoring circuits

In this test a resistor of value approximating the room temperature resistance of the PRTs is connected at the input of each PRT readout circuit, and the output code from the A/D converter is measured. The reference voltage used in the PRT readout circuits is also measured. Test data is presented on TDS 7.

4.4.4 Analog telemetry

In this test each of the analog telemetry signals is measured at the ANALOG HSKP jack on the TRU. Test data is presented on TDS 8.

4.5 Scan Drive

This test includes all CCAs involved in the scan drive function. The circuitry is programmed to provide one complete revolution of the drive motor as it steps through each of the thirty scene positions and the two calibration positions. The circuitry is programmed to park at the Warm Cal, Cold Cal, and the Nadir positions during the test sequence. The GSE test modes are also verified. To verify proper performance, the inertia disk on the motor shaft is visually observed through the one revolution and the various calibration positions. Test data is presented on TDS 9.

4.6 Supply Current

In this test, the total current drawn by the signal processor from each of the four supply voltages is measured with the signal processor fully populated with CCA's. Test data is presented on TDS 10.

5.0 TEST ANOMALIES

No test anomalies occurred during the Signal Processor engineering tests.

6.0 TEST RESULTS

The METSAT/AMSU A1 SIGNAL PROCESSOR TEST was successfully completed and all test data is within specified limits.

1-03

GENCORP AEROJET	MANUFACTURING ASSEMBLY INSTRUCTIONS (M.A.I.)			PAGE	OF
	PART DESCRIPTION SIGNAL PROCESSING ASSY.		PART NUMBER 1331670-2	6	7
PLANNED BY J. DIPASQUALE		DATE 5/08/97	REVISION 01	NEXT ASSEMBLY 1331720-2	
				OPER 0090	



5. Record Serial Numbers of each CCA below.

- d) Record S/N of each CCA in the area noted below, also record S/N on the Data Sheet.
Note: CCA'S will be installed at Operation 0120 per AE-26002/3 Test Procedure.
- e) Record Part No. and S/N of CCA required, for location J317 Connector.

LOCATION	ITEM #	CCA PART NO.	SERIAL NO.	DESCRIPTION	COMMENTS
J301					
J302					
J303	2	1338421-1	F19	TEMP. SENSOR A	
J304	3	1331682-1	F289	TEMP. SENSOR BD. "B"	
J305	3	1331682-1	F32	TEMP. SENSOR BD. "B"	
J306	4	1331688-1	F16	Temp.Sensor,ANLG MUX	
J307	5	1356418-1	F04	MUX AND ANLG/DGTL	
J308	6	1338424-1	F16	INTEG. & DUMP FILTER	
J309	6	1338424-1	F19	INTEG. & DUMP FILTER	
J310	6	1338424-1	F27	INTEG. & DUMP FILTER	
J311	6	1338424-1	F37	INTEG. & DUMP FILTER	
J312	7	1331147-1	F19	SPACECRAFT I/F NO.2	
J313	8	1331144-1	F19	SPACECRAFT I/F NO.1	
J314	9	1351150-1	F22	PARALLEL TO SER CNVTR	
J315	10	1331135-1	F11	TIMING AN CONTROL	
J316	11	1356413-2	F02	CPU	
J317	12	*1331126-11	F01	MEMORY ASSY.	**
J318	13	1331129-1	F16	SCAN CONTROL INTFC	
J319	40	1356911-1	F01	RELAY DRVR & CUR MON	
J320	14	1331697-1	F27	Interface/Converter	***
J321	15	1334972-1	F21	RSLVR DATA ISOL	
J322	16	1337739-1	F22	R-D CONVERTER/OSC	***
J323	14	1331697-1	F34	Interface/Converter	***
J324	15	1334972-1	F31	RSLVR DATA ISOL	
J325	16	1337739-1	F25	R-D CONVERTER/OSC	***
J326					
J327					

* = See table #1 for selection of CCA required at this location.

** = Memory CCA installed at next assembly.

670dash11

*** = Test and select resistors added at system level test.

Not Conformal Coated when installed at next assembly.

Figure #4

11 June 98

TEST DATA SHEET 1
A1 Continuity Tests (4.2.1)

From	To	Signal Name	Pass/Fail
J301-1	P511-3	CH 3 - IN	P
J301-10	P511-13	CH 8 - IN	P
J301-13	P511-15	CH 9 - IN	P
J301-15	P511-17	CH 10 - IN	P
J301-16	P511-19	CH 11 - IN	P
J301-19	P511-21	CH 12 - IN	P
J301-21	P511-23	CH 13 - IN	P
J301-22	P511-25	CH 14 - IN	P
J301-25	P511-1	CH 15 - IN	P
J301-3	P511-5	CH 4 - IN	P
J301-4	P511-7	CH 5 - IN	P
J301-60	E1	CHASSIS GND	P
J301-7	P511-9	CH 6 - IN	P
J301-9	P511-11	CH 7 - IN	P
J301-90	E2	CHASSIS GND	P
J304-43	P512-5	+15V(2)	P
J304-45	P512-24	+15V(2)	P
J304-46	P512-9	15VRTN(2/3)	P
J304-48	P512-29	15VRTN(2/3)	P
J304-49	P512-14	-15V(3)	P
J304-51	P512-15	-15V(3)	P
J305-68	P512-12	PRT35_HI (PRE AMP)	P
J305-72	P512-11	PRT35_LO (PRE AMP)	P
J326-76	E3	CHASSIS GND	P

Assembly No. 1331670-2 Shop Order No. 543651

Serial No. F03 Pass ☒ Fail ☐

Test Engineer D. Lusk 10/20/98 Quality Control [Signature] OCT 21 '98
(Signature) (Date) (Signature) (Date)

Customer Representative (Flight hardware only) [Signature] 10-21-98
(Signature) (Date)

TEST DATA SHEET 2
A1 Power Distribution (Paragraphs 4.2.2 & 4.2.3)

Power Supply Voltages:

+5.7 ± 0.1V: 5.672V
-15.7 ± 0.1V: -15.694V

+15.7 ± 0.1V: 15.683V
+28.7 ± 0.1V: 28.75V

Test Set-up Verified: YES ☒ NO ☐

Para. 4.2.3 Step No.	Connector No.	+5 ±0.5 V	P/F	+15 ±0.3V	P/F	-15 ±0.3V	P/F	+28 ±0.56V	P/F	+9 ±1V*	P/F
7*	J301									9.4	P
1	J303			14.98	P	-15.01	P				
2	J304			14.98	P	-15.00	P				
3	J305			14.98	P	-15.00	P				
4	J306			14.98	P	-15.00	P				
5	J307	4.95	P	14.98	P	-15.00	P				
5	J308			14.98	P	-15.00	P				
5	J309			14.98	P	-15.00	P				
5	J310			14.98	P	-15.00	P				
5	J311			14.98	P	-15.00	P				
5	J312	4.95	P							9.4	P
5	J313	4.95	P							9.4	P
5	J314	4.95	P								
5	J315	4.95	P								
5	J316	4.95	P								
5	J317	4.95	P								
5	J318	4.95	P								
5	J319	4.95	P	14.98	P	-15.01	P	28.05	P		
5	J320	4.96	P	14.98	P	-15.01	P				
5	J321	4.96	P								
5	J322	4.96	P	14.98	P	-15.00	P				
5	J323	4.96	P	14.98	P	-15.01	P				
5	J324	4.96	P								
5	J325	4.96	P	14.98	P	-15.01	P				
6	J327	4.96	P	14.98	P	-15.01	P	28.09	P		

*measured at paragraph 4.2.5.2. test

Assembly No. 1331670-2

Shop Order No. 543651

Serial No. F03

Pass ☒ Fail ☐

Test Engineer [Signature] 10/20/98
(Signature) (Date)

Quality Control [Signature] OCT 21 '98
(Signature) (Date)

Customer Representative (Flight hardware only) [Signature] 10-21-98
(Signature) (Date)

TEST DATA SHEET 3 (Sheet 1 of 2)
A1 Digital Processor (Paragraph 4.2.4)

CPU CCA Serial No. (J316) F02
Scan Control Interface CCA Serial No. (J318) F16
Timing and Control CCA Serial No. (J315) F11

4.2.4.1 Memory tests:

4.2.4.1/10 Circle Pass or Fail to indicate the result of the tests :

Pass Fail

If "Fail", record the error code and error description.

Error Code: N/A

Error Description: N/A

4.2.4.2 CPU tests:

4.2.4.2/10

	<u>Measurements</u>	<u>Limits</u>	<u>Pass/Fail</u>
V _{p-p}	<u>3.80V_{pp}</u>	3.30 - 4.94 V	<u>P</u>
T	<u>801.25</u>	761 - 841 ns	<u>P</u>

4.2.4.2/19 Circle Pass or Fail to indicate the result of the CPU tests

P
Pass Fail

4.2.4.3 Scan Control Interface Tests:

4.2.4.3/16 The input ports 0 and 1 tests

Pass Fail

4.2.4.3/23 Inhibit input port 0 and 1 tests

Pass Fail

4.2.4.3/35 The input ports 2 and 3 tests

Pass Fail

4.2.4.3/48² Inhibit input port 2 and 3 tests

Pass Fail

4.2.4.3/55 The output ports 0 and 1 tests

Pass Fail

TEST DATA SHEET 3 (Sheet 2 of 2)
A1 Digital Processor (Paragraph 4.2.4)

4.2.4.3 Scan Control Interface Tests (Cont):

4.2.4.3/63 The output ports 2 and 3 tests

Pass Fail

If "Fail", record the error code and error description.

Error Code:

N/A

Error Description:

N/A

4.2.4.4 Timing and Control Tests:

4.2.4.4/13	The Integrate and Hold pulse and the Dump pulse at the card rack slot J308.	<u>Pass</u>	Fail
4.2.4.4/23	The Integrate and Hold pulse and the Dump pulse at the card rack slot J309.	<u>Pass</u>	Fail
4.2.4.4/33	The Integrate and Hold pulse and the Dump pulse at the card rack slot J310.	<u>Pass</u>	Fail
4.2.4.4/43	The Integrate and Hold pulse and the Dump pulse at the card rack slot J311.	<u>Pass</u>	Fail
4.2.4.4/54	The Integrate and Hold pulse and the Dump pulse at the card rack slot J301.	<u>Pass</u>	Fail
4.2.4.4/64	The Antenna Strobe pulse test at J320.	<u>Pass</u>	Fail
4.2.4.4/68	The Antenna Strobe pulse test at J323.	<u>Pass</u>	Fail
4.2.4.4/78	The test of the interface to the Temp. Sensor Analog Mux card rack slot J306.	<u>Pass</u>	Fail
4.2.4.4/89	The test of the interface to the Analog Mux and Converter card rack slot J307.	<u>Pass</u>	Fail

If "Fail", record error code and error description:

Error Code:

N/A

Error Description:

N/A

Assembly No. 1331670-2

Shop Order No. 543651

Serial No. F03

Pass ✓ Fail

Test Engineer [Signature] 10/20/98
(Signature) (Date)

Quality Control [Signature] Oct 21 '98
(Signature) (Date)

Customer Representative (Flight hardware only) [Signature] 10-21-98
(Signature) (Date)

TEST DATA SHEET 4
A1 Relay Driver Tests (Paragraph 4.2.5.2)

Spacecraft Interface #2 CCA (J312) Ser. No. F19
Spacecraft Interface #1 CCA (J313) Ser. No. F19
Parallel to Serial Converter CCA (J314) Ser. No. F22
Relay Driver And Current Monitor CCA (J319) Ser. No. F01

Test Set-up Verified: Yes ☒ No ☐ STE Self Test: Pass ☒ Fail ☐

Step No.	Test Description	Pass/Fail
23	Module power connects	P
26	Survival heater power turns on	P
27	Survival heater power turns off	P
28	Module power disconnects	P
30	Scanner 1 power turns on	P
31	Scanner 2 power turns on	P
32	Scanner 1 power turns off	P
32	Scanner 2 power turns off	P
34	PLLO toggle	P
35	Module power disconnect	P

Assembly No. 1331670-2

Shop Order No. 543651

Serial No. F03

Pass ☒ Fail ☐

Test Engineer D. Lutz 10/20/98
(Signature) (Date)

Quality Control [Signature] OCT 21 '98
(Signature) (Date)

Customer Representative (Flight hardware only) [Signature] 10-21-98
(Signature) (Date)

TEST DATA SHEET 5
A1 Independence Of Measurements (Paragraph 4.2.6.1)

Analog Mux and A/D Converter CCA Serial No. F04

Test Set-up verified: YES ☒ NO ☐

<u>Supply</u>	<u>Measured Value (V)</u>	<u>Limits (V)</u>
+5	<u>4.806V</u>	+5 ± 0.25
+15	<u>15.89V</u>	+15 ± 1.0
-15	<u>-15.42V</u>	-15 ± 1.0

Integrate and Dump/Filter CCA Serial No.	Channel No.	Average for SIGNAL switch in HI position	Average for SIGNAL switch in LO position	Measurement Dependence ≤0.01%	Pass/Fail
F16	0	14171.3	14169.6	0.00259	P
	1	14168.9	14165.9	0.00458	P
	2	14176.6	14174.8	0.00275	P
	3	14174	14171.9	0.0032	P
F19	0	14155.9	14154.8	0.00168	P
	1	14143	14141.8	0.00183	P
	2	14154.9	14152.9	0.00305	P
	3	14162.7	14160.7	0.00305	P
F27	0	14105.6	14103.7	0.0029	P
	1	14106.9	14105	0.0029	P
	2	14095.9	14092.8	0.00473	P
	3	14120.9	14119	0.0029	P
F37	0	14181.7	14179	0.00412	P
	1	14175.7	14173.7	0.00305	P
	2	14170	14167.6	0.00366	P
	3	14178.8	14176.8	0.00305	P

Assembly No. 1331670-2

Shop Order No. 543651

Serial No. F03

Pass ☒ Fail ☐


Test Engineer [Signature] 10/20/98
(Signature) (Date)

Quality Control [Signature] Oct 21 '98
(Signature) (Date)

Customer Representative (Flight hardware only) [Signature] 10-21-98
(Signature) (Date)

TEST DATA SHEET 6 (Sheet 1 Of 2)
A1 Integrator Signal Multiplexing, And Digitization (Paragraph 4.2.6.2)

Analog Mux and A/D Converter CCA: Ser. No. F04
Integrate and Dump/Filter CCA: Ser. No. F16
Rack Slot J308: Ser. No. F19
Rack Slot J309: Ser. No. F27
Rack Slot J310: Ser. No. F37
Rack Slot J311: Ser. No. F37



Channel	Data	Data Limits	Data Pass/Fail	Integrator Waveform Pass/Fail
3	29265	27282 to 31076	P	P
4	29241	27282 to 31076	P	P
5	29114	27282 to 31076	P	P
6	29213	27282 to 31076	P	P
7	29218	27282 to 31076	P	P
8	29184	27282 to 31076	P	P
9	29007	27282 to 31076	P	P
10	29267	27282 to 31076	P	P
11	29233	27282 to 31076	P	P
12	29240	27282 to 31076	P	P
13	29109	27282 to 31076	P	P
14	29280	27282 to 31076	P	P
15	29256	27282 to 31076	P	P

TEST DATA SHEET 6 (Sheet 2 Of 2)
A1 Integrator Signal Multiplexing, And Digitization (Paragraph 4.2.6.2)

Signal Name	Output	Output Return	Signal Levels	- Pass/Fail
I/H	J301-42	J301-41	Pulses (TTL)	P
Dump	J301-45	J301-41	Pulses (TTL)	P
+5 Vdc GSE Interlock A	J301-61	J301-70	+5 V	P
+5 Vdc GSE Interlock B	J301-62	J301-70	+5 V	P

Assembly No. 1331670-2

Shop Order No. 543651

Serial No. F03

Pass ☒ Fail ☐

Test Engineer [Signature] 10/20/98
(Signature) (Date)

Quality Control [Signature] OCT 21 '98
(Signature) (Date)

Customer Representative (Flight hardware only) [Signature] 10-21-98
(Signature) (Date)

TEST DATA SHEET 7 (Sheet 1 of 2)
A1 Temperature Monitoring Circuits (Paragraph 4.2.6.3)

Temperature Sensor A CCA(J303) Serial No. F19
 Temperature Sensor B CCA (J304) Serial No. F27
 Temperature Sensor B CCA (J305) Serial No. F32
 Temperature Sensor Analog Mux CCA (J306) Serial No. F16

Dig. A Temp No.	Description	Data	Data Limits	Pass/Fail
1	Scan Motor A1-1	31310	28259 to 32513	P
2	Scan Motor A1-2	31415	28259 to 32513	P
3	Feedhorn A1-1	30499	28259 to 32513	P
4	Feedhorn A1-2	31296	28259 to 32513	P
5	RF MUX A1-1	31275	28259 to 32513	P
6	RF MUX A1-2	31375	28259 to 32513	P
7	LO CH 3	31520	28259 to 32513	P
8	LO CH 4	31367	28259 to 32513	P
9	LO CH 5	31615	28259 to 32513	P
10	LO CH 6	31345	28259 to 32513	P
11	LO CH 7	31398	28259 to 32513	P
12	LO CH 8	31158	28259 to 32513	P
13	LO CH 15	31375	28259 to 32513	P
14	PLO #2	31344	28259 to 32513	P
15	PLO #1	31416	28259 to 32513	P
16	N/A	N/A	N/A	N/A
17	Mixer IF CH 3	31446	28259 to 32513	P
18	Mixer IF CH 4	31082	28259 to 32513	P
19	Mixer IF CH 5	31317	28259 to 32513	P
20	Mixer IF CH 6	31208	28259 to 32513	P
21	Mixer IF CH 7	31359	28259 to 32513	P
22	Mixer IF CH 8	31282	28259 to 32513	P
23	Mixer IF CH 9/14	31650	28259 to 32513	P
24	Mixer IF CH 15	31241	28259 to 32513	P
25	IF Amp CH 11/14	31311	28259 to 32513	P
26	IF Amp CH 9	31398	28259 to 32513	P
27	IF Amp CH 10	31435	28259 to 32513	P
28	IF Amp CH 11	31551	28259 to 32513	P
29	DC/DC Conv	31185	28259 to 32513	P
30	IF Amp CH 13	31386	28259 to 32513	P
31	IF Amp CH 14	31383	28259 to 32513	P
32	IF Amp CH 12	31583	28259 to 32513	P
33	RF Shelf A1-1	31190	28259 to 32513	P
34	RF Shelf A1-2	28387	28259 to 32513	P
35	Detector/Preamp	31295	28259 to 32513	P

TEST DATA SHEET 7 (Sheet 2 of 2)
A1 Temperature Monitoring Circuits (Paragraph 4.2.6.3)

Dig. A Temp No.	Description	Data	Data Limits	Pass/Fail
36	A1-1 Warm Load 1	22552	20339 to 23401	P
37	A1-1 Warm Load 2	22719	20339 to 23401	P
38	A1-1 Warm Load 3	22751	20339 to 23401	P
39	A1-1 Warm Load 4	22831	20339 to 23401	P
40	A1-1 Warm Load C	22711	20339 to 23401	P
41	A1-2 Warm Load 1	22587	20339 to 23401	P
42	A1-2 Warm Load 2	22687	20339 to 23401	P
43	A1-2 Warm Load 3	22886	20339 to 23401	P
44	A1-2 Warm Load 4	22440	20339 to 23401	P
45	A1-2 Warm Load C	22739	20339 to 23401	P
46	Thermal Reference	25402	23340 to 26320	P

Assembly No. 1331670-2

Shop Order No. 543651

Serial No. F03

Pass ☒ Fail ☐

Test Engineer [Signature] 10/20/98
(Signature) (Date)

Quality Control [Signature] OCT 21 '98
(Signature) (Date)

Customer Representative (Flight hardware only) [Signature] 10-21-98
(Signature) (Date)

TEST DATA SHEET 8
A1 Analog Telemetry (Paragraph 4.2.6.4)

ANALOG HSKP Switch Position	DVM Reading (V)	Limits (V)	Pass/Fail
1	2.98	2.85 to 3.15	P
2	3.455	3.30 to 3.66	P
3	2.968	2.87 to 3.17	P
4	3.001	2.85 to 3.15	P
5	3.452	3.30 to 3.66	P
6	2.982	2.87 to 3.17	P
7	3.449	3.30 to 3.66	P
8	2.976	2.87 to 3.17	P
9	2.979	2.85 to 3.15	P
10	3.569	3.42 to 3.78	P
11	3.263	3.13 to 3.45	P
12	2.963	2.84 to 3.14	P
13	2.955	2.84 to 3.14	P
14	2.961	2.84 to 3.14	P
15	2.967	2.84 to 3.14	P
16	2.970	2.84 to 3.14	P
17	2.966	2.84 to 3.14	P
18	3.447	3.30 to 3.66	P
19	0.05	4.30 to 4.66 ^{-0.1 to 0.1}	P
19	-4.035	0.4 to 0.48 ^{-3.7 to -4.3}	P
20	0.059	4.30 to 4.66 ^{-0.1 to 0.1}	P
20	-4.025	0.4 to 0.48 ^{-3.7 to -4.3}	P
21	0.006	-0.05 to 0.05	P
21	2.963	2.8 to 3.4	P
22	0.017	-0.05 to 0.05	P
22	2.970	2.8 to 3.4	P

1964
9/28/98
Q3
228

Assembly No. 1331670-2

Shop Order No. 543651

Serial No. F03

Pass ✓ Fail

Test Engineer [Signature] 10/20/98
(Signature) (Date)

Quality Control [Signature] OCT 21 '98
(Signature) (Date)

Customer Representative (Flight hardware only) [Signature] 10-21-98
(Signature) (Date)

TEST DATA SHEET 9
A1 Scan Drive/ Signal Processor Tests (Paragraph 4.3.1 And 4.3.2)

A1-1 Drive Subsystem CCAs:

Interface Converter CCA (J320) Ser. No. F27
Resolver Data Isolator CCA (J321) Ser. No. F21
R/D Converter/Oscillator CCA (J322) Ser. No. F22
Motor Drive 3-Hall Sensor CCA (J323) Ser. No. F04
Test Set-up Verified: Yes ☒ No ☐

19 Feb 9/28/98
QC
229

Para/Step No.	Mode	Pass/Fail
4.3.1.2.1/11	Motor in warm cal position	P
4.3.1.2.2/3	Motor in nadir position	P
4.3.1.2.3/2	Motor in cold cal position 1	P
4.3.1.2.3/3	Motor in cold cal position 2	P
4.3.1.2.3/4	Motor in cold cal position 3	P
4.3.1.2.3/5	Motor in cold cal position 4	P
4.3.1.2.4/5	Motor in full scan mode	P
4.3.1.2.5/9	GSE mode 2	P
4.3.1.2.6/4	GSE mode 4	P
4.3.1.2.7/4	GSE mode 5	P
4.3.1.2.8/4	GSE mode 1	P
4.3.1.2.9/4	GSE mode 3	P
4.3.1.2.9/7	GSE mode 7	P
4.3.1.2.10/2	Scan power off	P

A1-2 Drive Subsystem CCAs:

Interface Converter CCA (J323) Ser. No. F34
Resolver Data Isolator CCA (J324) Ser. No. F31
R/D Converter/Oscillator CCA (J325) Ser. No. F25
Motor Drive 3-Hall Sensor CCA (J326) Ser. No. F11
Test Set-up Verified: Yes ☒ No ☐

19 Feb 9/28/98
QC
229

Para. No/Step No.

4.3.2.2 A1-2 scan drive operates in full scan mode. Pass ☒ Fail ☐

Assembly No. 1331670-2

Shop Order No. 543651

Serial No. P03

Pass ☒ Fail ☐

Test Engineer [Signature] 10/2/98
(Signature) (Date)

Quality Control [Signature] OCT 21 '98
(Signature) (Date)

Customer Representative (Flight hardware only) [Signature] 10-21-98
(Signature) (Date)

TEST DATA SHEET 10
A1 Supply Currents (Paragraph 4.4)

Voltages	Measured Current	Limits (in mA)	Pass/Fail
+28.7V	7.55	6 to 12	P
+5.7V	660	700 to 1642 550 to 900	P
+15.7V	197	152 to 364	P
-15.7V	192	162 to 381	P

D.L.
9/28/98
CC
229

Assembly No. 1331670-2

Shop Order No. 543651


Serial No. F03

Pass ☒ Fail ☐

Test Engineer *D.L.* 10/20/98
(Signature) (Date)

Quality Control *[Signature]* OCT 21 '98
(Signature) (Date)

Customer Representative (Flight hardware only) *[Signature]* 10-21-98
(Signature) (Date)

 NASA National Aeronautics and Space Administration				Report Documentation Page			
1. Report No. ---		2. Government Accession No. ---		3. Recipient's Catalog No. ---			
4. Title and Subtitle Integrated Advanced Microwave Sounding Unit-A (AMSU-A), Engineering Test Report				5. Report Date 28 October 1998			
				6. Performing Organization Code ---			
7. Author(s) D. Lund				8. Performing Organization Report No. 11302			
				10. Work Unit No. ---			
9. Performing Organization Name and Address Aerojet 1100 W. Hollyvale Azusa, CA 91702				11. Contract or Grant No. NAS 5-32314			
				13. Type of Report and Period Covered Final			
12. Sponsoring Agency Name and Address NASA Goddard Space Flight Center Greenbelt, Maryland 20771				14. Sponsoring Agency Code ---			
15. Supplementary Notes ---							
16. ABSTRACT (Maximum 200 words) This is the Engineering Test Report, METSAT A1 Signal Processor (P/N 1331670-2, S/N F03), for the Integrated Advanced Microwave Sounding Unit-A (AMSU-A).							
17. Key Words (Suggested by Author(s)) EOS Microwave System				18. Distribution Statement Unclassified — Unlimited			
19. Security Classif. (of this report) Unclassified		20. Security Classif. (of this page) Unclassified		21. No. of pages ---			
				22. Price ---			

NASA FORM 1626 OCT 86

PREPARATION OF THE REPORT DOCUMENTATION PAGE

The last page of a report facing the third cover is the Report Documentation Page, RDP. Information presented on this page is used in announcing and cataloging reports as well as preparing the cover and title page. Thus, it is important that the information be correct. Instructions for filling in each block of the form are as follows:

Block 1. Report No. NASA report series number, if preassigned.

Block 2. Government Accession No. Leave blank.

Block 3. Recipient's Catalog No. Reserved for use by each report recipient.

Block 4. Title and Subtitle. Typed in caps and lower case with dash or period separating subtitle from title.

Block 5. Report Date. Approximate month and year the report will be published.

Block 6. Performing Organization Code . Leave blank.

Block 7. Authors. Provide full names exactly as they are to appear on the title page. If applicable, the word editor should follow a name.

Block 8. Performing Organization Report No. NASA installation report control number and, if desired, the non-NASA performing organization report control number.

Block 9. Performing Organization Name and Address. Provide affiliation (NASA program office, NASA installation, or contractor name) of authors.

Block 10. Work Unit No. Provide Research and Technology Objectives and Plants (RTOP) number.

Block 11. Contract or Grant No. Provide when applicable.

Block 12. Sponsoring Agency Name and Address. National Aeronautics and Space Administration, Washington, D.C. 20546-0001. If contractor report, add NASA installation or HQ program office.

Block 13. Type of Report and Period Covered. NASA formal report series; for Contractor Report also list type (interim, final) and period covered when applicable.

Block 14. Sponsoring Agency Code. Leave blank.

Block 15. Supplementary Notes. Information not included

elsewhere: affiliation of authors if additional space is required for Block 9, notice of work sponsored by another agency, monitor of contract, information about supplements (file, data tapes, etc.) meeting site and date for presented papers, journal to which an article has been submitted, note of a report made from a thesis, appendix by author other than shown in Block 7.

Block 16. Abstract. The abstract should be informative rather than descriptive and should state the objectives of the investigation, the methods employed (e.g., simulation, experiment, or remote sensing), the results obtained, and the conclusions reached.

Block 17. Key Words. Identifying words or phrases to be used in cataloging the report.

Block 18. Distribution Statement. Indicate whether report is available to public or not. If not to be controlled, use "Unclassified-Unlimited." If controlled availability is required, list the category approved on the Document Availability Authorization Form (see NHB 2200.2, Form FF427). Also specify subject category (see "Table of Contents" in a current issue of STAR) in which report is to be distributed.

Block 19. Security Classification (of the report). Self-explanatory.

Block 20. Security Classification (of this page). Self-explanatory.

Block 21. No. of Pages. Count front matter pages beginning with iii, text pages including internal blank pages, and the RDP, but not the title page or the back of the title page.

Block 22. Price Code. If Block 18 shows "Unclassified-Unlimited," provide the NTIS price code (see "NTIS Price Schedules" in a current issue of STAR) and at the bottom of the form add either "For sale by the National Technical Information Service, Springfield, VA 22161-2171" or "For sale by the Superintendent of Documents, U.S. Government Printing Office, Washington, D.C. 20402-0001," whichever is appropriate.

REPORT DOCUMENTATION PAGE			Form Approved OMB No. 0704-0188	
Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.				
1. AGENCY USE ONLY (Leave blank)		2. REPORT DATE		3. REPORT TYPE AND DATES COVERED
4. TITLE AND SUBTITLE Integrated Advanced Microwave Sounding Unit-A (AMSU-A), Engineering Test Report			5. FUNDING NUMBERS NAS 5-32314	
6. AUTHOR(S) D. Lund				
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) Aerojet 1100 W. Hollyvale Azusa, CA 91702			8. PERFORMING ORGANIZATION REPORT NUMBER 11302 28 October 1998	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES) NASA Goddard Space Flight Center Greenbelt, Maryland 20771			10. SPONSORING/MONITORING AGENCY REPORT NUMBER ---	
11. SUPPLEMENTARY NOTES ---				
12a. DISTRIBUTION/AVAILABILITY STATEMENT ---			12b. DISTRIBUTION CODE ---	
13. ABSTRACT (Maximum 200 words) This is the Engineering Test Report, METSAT A2 Signal Processor (P/N 1331670-2, S/N F03), for the Integrated Advanced Microwave Sounding Unit-A (AMSU-A).				
14. SUBJECT TERMS EOS Microwave System			15. NUMBER OF PAGES	
			16. PRICE CODE ---	
17. SECURITY CLASSIFICATION OF REPORT Unclassified	18. SECURITY CLASSIFICATION OF THIS PAGE Unclassified	19. SECURITY CLASSIFICATION OF ABSTRACT Unclassified	20. LIMITATION OF ABSTRACT SAR	

GENERAL INSTRUCTIONS FOR COMPLETING SF 298

The Report Documentation Page (RDP) is used in announcing and cataloging reports. It is important that this information be consistent with the rest of the report, particularly the cover and title page. Instructions for filling in each block of the form follow. It is important to stay within the lines to meet optical scanning requirements.

Block 1. Agency Use Only(Leave blank)

Block 2. Report Date Full publication date including day, month, and year, if available (e.g., 1 Jan 88). Must cite at least the year.

Block 3. Type of Report and Dates Covered State whether report is interim, final, etc. If applicable, enter inclusive report dates (e.g., 10 Jun 87 - 30 Jun 88).

Block 4. Title and Subtitle A title is taken from the part of the report that provides the most meaningful and complete information. When a report is prepared in more than one volume report the primary title, add volume number and include subtitle for the specific volume. On classified documents enter the title classification in parentheses.

Block 5. Funding Numbers To include contract and grant numbers; may include program element number(s), project number(s), task number(s), and work unit number(s). Use the following labels:

C	-	Contract	PR	-	Project
G	-	Grant	TA	-	Task
PE	-	Program Element	WU	-	Work Unit Accession No.

Block 6. Author(s) Name(s) of person(s) responsible for writing the report, performing the research, or credited with the content of the report. If editor or compiler, this should follow the name(s).

Block 7. Performing Organization Name(s) and Address(es) Self-explanatory.

Block 8. Performing Organization Report Number Enter the unique alphanumeric report number(s) assigned by the organization performing the report.

Block 9. Sponsoring/Monitoring Agency Name(s) and Address(es) Self-explanatory.

Block 10. Sponsoring/Monitoring Agency Reports Number (if known).

Block 11. Supplementary Notes Enter information not included elsewhere such as: Prepared in cooperation with ...; Trans. of ...; To be published in ... When a report is revised, include a statement whether the new report supersedes or supplements the older report.

Block 12.a Distribution/Availability Statement Denotes public availability or limitations. Cite any availability to the public. Enter additional limitations or special markings in all capitals (e.g., NOFORN, REL, ITAR).

DOD - See DoDD 5230.24 *Distribution Statement on Technical Documents*

DOE - See authorities.

NASA - See Handbook NHB 2200.2.

NTIS - Leave blank.

Block 12.b Distribution Code.

DOD - Leave blank.

DOE - Enter DOE distribution categories from the standard Distribution for Unclassified Scientific and Technical Reports.

NASA - Leave blank.

NTIS - Leave blank.

Block 13. Abstract Include a brief *Maximum 200 words* factual summary of the most significant information contained in the report.

Block 14. Subject Terms Keywords or phrases identifying major subjects in the report.

Block 15. Number of Pages Enter the total number of pages.

Block 16. Price Code Enter appropriate price code (NTIS only).

Block 17 - 19. Security Classifications Self-explanatory. Enter U.S. Security Classification in accordance with U.S. Security Regulations (i.e., UNCLASSIFIED). If form contains classified information, stamp classification on the top and bottom of the page.

Block 20. Limitation of Abstract This block must be completed to assign a limitation to the abstract. Enter either UL (unlimited) or SAR (same as report). An entry in this block is necessary if the abstract is to be limited. If blank, the abstract is assumed to be unlimited.



DOCUMENT APPROVAL SHEET

TITLE Engineering Test Report METSAT A1 Signal Processor (P/N 1331670-2, S/N F03)		DOCUMENT NO. Report 11302 28 October 1998	
INPUT FROM: D. Lund	DATE	CDRL: 207	SPECIFICATION ENGINEER: N/A
CHECKED BY: N/A	DATE	JOB NUMBER: N/A	DATE
APPROVED SIGNATURES		DEPT. NO.	DATE
Product Team Leader (A. Nieto) <u><i>A. Nieto</i></u>		8341	11/2/98
Systems Engineer (R. Platt) <u><i>R. Platt</i></u>		8311	11/2/98
Design Assurance (E. Lorenz) <u><i>E. Lorenz</i></u>		8331	11/2/98
Quality Assurance (R. Taylor) <u><i>R. Taylor</i></u>		7831	11-2-98
Technical Director/PMO (R. Hauerwaas) <u><i>R. Hauerwaas</i></u>		4001	12/3/98
Released: Configuration Management (J. Cavanaugh) <u><i>J. Cavanaugh</i></u>		8361	12/3/98
By my signature, I certify the above document has been reviewed by me and concurs with the technical requirements related to my area of responsibility.			
(Data Center) FINAL			
Please return this sheet and the reproducible master to Jim Kirk (Bldg. 1/Dept. 8631), ext. 2081.			